

SPECS

	TELAIO FRAME	FORCELLA FORK	CAMBIO GEAR	GUARNITURA CHAINWHEEL	COMANDI SHIFTING LEVERS	CASSETTA CASSETTE	DERAGLIATORE FRONT DERAILLEUR	MOZZI HUBS	CERCHI RIMS	PNEUMATICI TYRES	FRENI BRAKES	PIEGA HANDLEBAR	PIANTONE STEM	CANNOTTO SEAT POST	SELLA SADDLE
719AMEB	RIBOT A SHIMANO XT bis 2x11	ROCK SHOX RECON BOOST	SHIMANO XT M8000	SHIMANO XT M8000 36/26 BOOST	SHIMANO XT M8000	SUNRACE 11/40	SHIMANO XT M8025	KT	NO TUBES ZTR RAPID	SCHWALBE RAPID ROB	SHIMANO M506	TORPADO ALUMINIUM	TORPADO ALUMINIUM	TORPADO ALUMINIUM	SELLE ITALIA Q-BIK
719ALEB	RIBOT A SHIMANO SLX/XT 2x11	ROCK SHOX RECON BOOST	SHIMANO XT M8000	SHIMANO SLX M7000 36/26 BOOST	SHIMANO SLX M7000	SUNRACE 11/40	SHIMANO SLX M7025	KT	NO TUBES ZTR RAPID	SCHWALBE RAPID ROB	FORMULA C1	TORPADO ALUMINIUM	TORPADO ALUMINIUM	TORPADO ALUMINIUM	SELLE ITALIA Q-BIK
719AFEB	RIBOT A SRAM NX 1x11	ROCK SHOX RECON BOOST	SRAM NX	SRAM NX 30T BOOST	SRAM NX TRIGGER	SRAM XG-1130 11/42		KT	NO TUBES ZTR RAPID	SCHWALBE RAPID ROB	SHIMANO M355	TORPADO ALUMINIUM	TORPADO ALUMINIUM	TORPADO ALUMINIUM	SELLE ITALIA Q-BIK

DISPONIBILE ANCHE CON TELAIO NEARCO A+ IN VERSIONE 29"
AVAILABLE ALSO WITH NEARCO A+ FRAME, 29" WHEELS



SPECIFICATIONS		SMALL	MEDIUM	LARGE	X-LARGE
A	Seat Tube Length (mm)	380	430	480	530
F	Top Tube Horizontal (mm)	555	585	610	630
D	Head Tube Length (mm)	90	100	110	120
E	Seat Tube Angle Effective (°)	73°	73°	73°	73°
C	Head Tube Angle (°)	70°	70°	70°	70°
FC	Front Centre (mm)	618	648	674	694
RC	Chain Stay Length (mm)	440	440	440	440
WB	WheelBase (mm)	1050	1081	1106	1127
BB HEIGHT	Bottom Bracket Height (mm)	310	310	310	310
STACK	Stack (mm)	599	609	618	628
REACH	Reach (mm)	372	399	421	438

